

DIGITAL LIGHT METER (LUX / FC / CD) MS6612 / MS6612T



MS6612

LUX RANGE
200000

FC RANGE
20000

AUTO **Apo**

MAX MIN **REL** **PEAK**

ZERO **H** **☐**



OPEN

MS6612T

LUX RANGE
200000

FC RANGE
20000

CD RANGE
999900

AUTO **Apo**

MAX MIN **REL** **PEAK**

ZERO **L.S.** **H**



Specifications

MS6612

Specifications	Range	Resolution	Accuracy
Measurement Range	0~200000Lux	0.01Lux	±(3%+2)
	0~20000FC	0.01FC	±(3%+2)

Features

D splay	counts	2000
Auto ranging	Auto & Manual	●
APO	Auto Power Off	●
MAX/MIN		●
REL	Relative Measurement	●
PEAK	Peak Measurement	●
ZERO	Zero Calibration	●
FC/Lux	FC/Lux Unit Selection	●
Data Hold		●
Backlight	Display Backlight	●
Analog Bar	Analog Bar Indication	●
LBD	Low Battery Display	●

General

Power Supply	1x9V 6F22 Battery
Product Size	170mm×89mm×43mm/6.7"×3.5"×1.7"
Product Weight	177g/0.39lb
Safety Rating	CE(EMC) RoHS

Specifications

MS6612T

Specifications	Range	Resolution	Accuracy
Measurement Range	0~200000Lux	0.01Lux	±(3%+2)
	0~20000FC	0.01FC	±(3%+2)
	0~999900CD	0.01CD	±(3%+2)

Light Source Default Values	L0-Standard Lighting	●
	L1-LED Daytime Light	●
	L2-LED Red Light	●
	L3-LED Amber(yellow) Light	●
	L4-LED Green Light	●
	L5-LED Blue Light	●
	L6-LED Purple Light	●
	L7-L9-Default Standard Lighting	●

Features

D splay	counts	2000
Auto ranging	Auto & Manual	●
APO	Auto Power Off	●
MAX/MIN		●
REL	Relative Measurement	●
PEAK	Peak Measurement	●
ZERO	Zero Calibration	●
FC/Lux/CD	FC/Lux/CD Unit Selection	●
Data Hold		●
Backlight	Display Backlight	●
Analog Bar	Analog Bar Indication	●
LBD	Low Battery Display	●

General

Power Supply	1x9V 6F22 Battery
Product Size	170mm×89mm×43mm/6.7"×3.5"×1.7"
Product Weight	177g/0.39lb
Safety Rating	CE(EMC) RoHS

